Reversible Plate Compactors

- Working width 50-75 cm.
- Infinitely variable hydraulically controlled forward and reverse compaction.
- Self tightening clutch system for long v-belt life.
- Reinforced and strengthened base plate, especially designed for tough jobs.
- Long life, High quality brass cage bearings.
- Newly designed gearbox, allowing easy and quick maintenance.
- Handle locks in one swift motion, allowing easy transport in the upright position.
- New cage and engine box, strong and robust for the toughest jobs.
- New extra strong anti-vibration mounting brackets.
- Easy to use and easy to mount transport wheels (Optional only for RP2414/RP3014).



SPECIFICATIONS

Model	RP2	2414 F		RP3014		RP4		014		RP6514	
Engine	GX160	IB20	GX200	IB20		GX270		IB30		IB50	
Туре	Petrol	Diesel	Petrol	Diesel		Petrol		Diesel		Diesel	
Maker	Honda	Hatz	Honda	Hatz		Honda		Hatz		Hatz	
HP	5	4.5	5.5	4.5		9		7.6		10.9	
Working Width (mm)	500	500	500	500	600	500	600	500	600	600	750
Vibration Plate Length (mm)	680	680	710	710		840		840		900	
Vibration frequency (Hz)	92	92	81	81		79		79		71	
Max. Traveling Spead (m/min)	20	20	20	20		20		20		25	24
Compaction area m ² /hr	600	600	600	600	720	600	720	600	720	990	1122
Centrifugal For ce (Kg)	2400	2400	3000	3000		4000		4000		6500	
Weight (kg)	149	164	181	196**	206**	265	275	275	285	420*	445*

* Including electric starter. For models without electric starter weight is less 20 Kg.

** For models with an electric starter weight is extra 15 Kg.