



**Multi-headed floor scabbler gives 24,000 light blows per minute**

## Unique design ...

## Highly productive method of concrete keying & laitance removal

The Trelawny MHS11 is unique in its design, developed in conjunction with the 'CITB - Construction Industry Training Board'.

It offers a low vibration machine of heavy body but giving over 24,000 light blows per minute.

This unique combination delivers the ultimate productivity of 30m<sup>2</sup>/hour plus in scabbling & laitance removal without damaging the substrate below.



## FEATURES

- **Compact design:** Easily transportable
- **Tough tool:** Designed for use in construction
- **Dust Free Working:** Available with optional vacuum shroud
- **Low vibration:** 3 point vibration damping system for operator comfort (4.96m/s<sup>2</sup>)
- **Low air consumption:** Will operate from a small single tool compressor (55cfm / 26 litres/second)

## CONSUMABLES

Applications	Used with consumables:	Part No.	To suit models
<ul style="list-style-type: none"> <li>✓ Laitance removal from large floor areas</li> <li>✓ Roughing concrete prior to resurfacing</li> </ul>	 <p>One piece piston tungsten carbide tipped bush hammer head</p>	<b>612.0125</b>	<b>159.6050</b> <b>159.6051</b>
<ul style="list-style-type: none"> <li>✓ Bridge deck preparation for 'waterproofing'</li> </ul>	 <p>Replaceable cutter head tungsten carbide tipped bush hammer</p>	<b>426.5355</b>	<b>159.6000</b>
<ul style="list-style-type: none"> <li>✓ Levelling floors</li> <li>✓ Reducing concrete</li> <li>✓ Removal of floor paints &amp; coatings</li> </ul>	 <p>Replaceable cutter head tungsten carbide tipped cruciform head</p>	<b>426.5358</b>	<b>159.6100</b>
	Piston to fit replaceable head	<b>612.0120</b>	<b>159.6000</b> <b>159.6100</b>



## TVS™ - Trelawny Vacuum System

Where control of nuisance and hazardous dust is necessary Trelawny MHS11 can be used with:

-optional vacuum shroud

**Part No: 437.0120**

-and pneumatic dust collector

**Part No: 303.10KAV45 / D**



**MHS11 with dust shroud ( 437.0120 )**



**Dust collector ( 303.10KAV45/D )**

**ATEX approved**  
for use in  
gas zone 2  
&  
dust zone  
22

**Alternative electric vacuums available – ask for details**

## TECHNICAL DATA

Model	Part Number	Weight (kg)	Length (mm)	Height (mm)	Width (mm)	Cutting width (mm)	B.P.M (Blows per minute)	Air Consum. (litres per second – cubic feet per minute)	Noise Level db(A)	Vibration Level Aeq m/s <sup>2</sup>
<b>MHS11</b>	159.6050	70	340	1290	285	250	11 x 2200	26 lps (55cfm)	97	4.96
<b>MHS11 With Dust Shroud</b>	159.6051	72	340	1290	285	250	11 x 2200	26 lps (55cfm)	97	4.96

Designates tools & machines which can be used with Trelawny range of dust collectors for the containment of hazardous & nuisance dust

Always look for the Vibro-Lo label on tools designed to reduce the risk of vibration related injuries